

Sanitary Clamp Non-Retention Ball Valve

卫生级无滞留球阀

Product Information 产品信息

Clamp non-retention ball valve is an all-inclusive ball seat design, which solves the problem of liquid retention in the valve cavity of the ball valve. Body combination clamp connection which easy to dismantle the ball valve without any professional tools.

无滞留球阀为全包式球座设计，解决了液体滞留在球阀腔内的问题。卡箍式链接球阀，轻松的拆卸球阀无需任何专业工具。

- Operation: Manual
操控：手动
- Working Temperature : -20°C to +135°C
工作温度：-20°C to +135°C
- Sterilization Temperature : 150°C (max 20mins)
灭菌温度：150°C (最高20分钟)
- Working Pressure : 1.6Mpa (16 Bar)
工作压力：1.6Mpa (16 Bar)
- Steel Material: 304 / 316L
金属材质：304/316L
- Seal Material : Teflon
密封圈材质：四氟乙烯
- Size: 1" to 4"
(other sizes available on request)



Clamp Non-Retention Ball Valve- Ferrule End

无滞留球阀球阀-快接头

Size	d	D	L	H	S
1.0"	22.4	50.5	110.0	70.0	105.0
1.5"	35.1	50.5	140.0	80.0	150.0
2.0"	47.8	64.0	164.0	85.0	160.0
2.5"	59.5	77.5	180.0	110.0	180.0
3.0"	72.0	91.0	190.0	130.0	200.0
4.0"	98.0	119.0	220.0	155.0	230.0

